

Katalogový list


platný od: 1/1/22

+GF+



Elektro T-kus rovnoramenný, redukovaný

- PE 100 SDR 11 (ISO S5)
- 10 bar plyn / 16 bar voda
- 4mm svařovací konektory
- Kontrolní výronek s ochranou proti vytečení taveniny
- * dvě oddělené svařovací zóny



d	d2	obj. číslo	hmotn.	d1	L	L1	z	z1	H	SDR trubky
(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
110	90	753 211 034	1.652	140	255	72	56	245	80	9-17.6
125	90	753 211 035	2.242	156	276	75	53	245	80	9-17.6
140	63	753 901 867	2.879	185	300	83	67	220	80	9-17.6
140	75	753 901 868	2.938	185	300	83	67	230	90	9-17.6
140	90	753 901 869	3.044	185	300	83	67	235	95	9-17.6
140	110	753 901 870	3.234	185	300	83	67	245	105	9-17.6
160	63	753 211 025	3.700	208	330	89	76	178	63	11-17.6
160	90	753 211 026	3.900	208	330	89	76	209	94	11-17.6
160	110	753 211 027	4.000	208	330	89	76	219	104	11-17.6
*	200	90	753 211 059	250	595	104	194	216	81	11-26
*	200	110	753 211 060	250	600	104	194	219	84	11-26
*	200	160	753 211 063	250	595	104	194	237	101	11-26
*	225	90	753 211 069	280	666	112	217	228	80	11-26
*	225	110	753 211 070	280	670	112	217	238	85	11-26
*	225	160	753 211 073	280	667	112	217	258	105	11-26
*	250	110	753 211 080	310	709	123	220	284	85	11-26
*	250	160	753 211 083	310	711	123	220	266	101	11-26

Technické údaje jsou nezávazné. Konstrukční a rozměrové změny vyhrazeny.
Platí naše všeobecné obchodní podmínky.